



*TO BE MEASURED ON LONGEST SIDE ONLY WITH THE WIRE IN INTIMATE CONTACT WITH THE BOTTOM OF THE GLASS WEDGE.

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	*MSCP ±25%	*LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
127	2.47	.275	.48	6.03	30	C-2R
159	6.3	.150	.33	4.15	20,000	C-2R
259	6.3	.250	.65	8.17	10,000	C-2R
555	6.3	.250	.90	11.31	3,000	C-2R
658	14.0	.080	.31	3.90	15,000	C-2F
161	14.0	.190	1.00	12.57	4,000	C-2F
158	14.0	.240	2.00	25.14	500	C-2V
194	14.0	.270	2.00	25.14	2,500	C-2F
193	14.0	.330	2.00	25.14	7,500	C-2F
168	14.0	.350	3.00	37.71	1,500	C-2F
585	28.0	.040	.30	3.77	7,000	C-2F
656	28.0	.060	.62	7.79	2,500	C-2F
657	28.0	.080	.62	7.79	15,000	C-2F
400	28.0	.100	1.60	20.11	1,000	C-2F
464	28.0	.170	3.00	37.71	1,500	C-2F
655	28.0	.200	3.00	37.71	7,000	C-2F
Custom	8	.250	1.0	12.57	10,000	C-2R

		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0					
		THIRD ANGLE PROJECTION		TITLE T-3 1/4 STANDARD GLASS WEDGE BASE			
A DELETE REPEATED DIM. RELEASED & CANCEL GW-STD-T3 1/4, 447 & 509		3/26/01 5/17/00		DRAWN BY L. WENGSTROM		APPVD BY DATE J.K. 3/26/01	
REV. NO. DESCRIPTION/ECO NUMBER		APPVD DATE		SIZE A		FSCM NO. 55335	
		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		DRAWING NO. GLASS WEDGE BASE T-3 1/4	
				RELEASED DATE 5/17/00		REVISION DATE 3/25/01	
				REV. NO. A		SHEET 1 OF 1	